

© C-One BASE



FULL SET OF FUNCTIONS
AND OPTIONS



POWER PRE-STRETCH
CARRIAGE



GREAT VALUE FOR MONEY



C-One Base is designed
to offer a superb
price/quality ratio
in a sturdy product
with a complete range
of features.

C-One Base is the perfect balance between low price, sturdiness, ease of use and completeness of functions. But in this machine there is room for innovation as well: for example, in the new carriage without rollers and with electro-magnetic brake system, that allows for quick load of the film coil, or in the new control panel, with an intuitive system to set programs and parameters, or in the new electronic board with included inverters.

A "rack and pinion" system moves the carriage up and down, giving to the machine great safety and toughness: an exclusive innovation of C-One machines.

Thanks to available options, even heavy/big/unstable loads can be wrapped, machine can be loaded even by a hand pallet truck and it can have power pre-stretch.

There's plenty of solutions in C-One Base little price!

Technical Data

- ↕ Height: 2468 mm.
- ↔ Width: 1500 mm.
- ↗ Length: 2380 mm.
- ↑ Turntable height from ground level: 86 mm.
- 📦 Weight: 400 kg.
- 🔌 Power Supply: 220 Vac 1P+N
(other options: 220 Vac 3PH+N o 400 Vac 3PH+N)
- ⚡ Power absorption: 0,5 KW

Product Specifications



- Machine cycle controlled by electronic board
- Frequency controller to adjust separately the ascent and descent speed of the carriage
- Frequency controller to adjust the turntable speed
- Turntable \varnothing .1500 mm
- Maximum pallet height: 2300 mm
- Maximum pallet dimensions 800x1200 mm
- Maximum pallet weight 1200 kg
- Electromagnetic brake to stretch the film
- Photocell to detect the height of the pallet
- Safety stop at the bottom of the carriage
- Stop at 0 position
- IP54 control panel
- 3 Password levels
- Adjustable parameters by the control panel without password: cycle selection, number of laps (bottom and top), topsheet cycle parameters, rotation speed, carriage ascent speed, carriage descent speed, wrapping height in cm, film tension, initial wrapping height
- 5 Working cycles: ascent/descent; topsheet; only ascent; only descent; layers
- Storage of 32 user programs
- 3 Operating modes: semimanual, semiautomatic, fixed height
- Strengthening operation
- Acoustic warning at the cycle beginning and stop
- Auto diagnostic
- Wrapped pallet counter (with password)
- Full configuration possible at 3rd password level
- Infrared/radio remote control receiver
- Powder coating
- Still turntable at the end of the cycle
- 2 Years warranty

Main Options

- Electrical top-press unit for unstable loads
- Power pre-stretch carriage
- Wrapping height up to 2.8 mt
- 1800 mm diameter turntable
- 1650 mm diameter turntable
- 2000 kg load
- Remote Control
- Ramp
- Pit frame
- Black loads photocell
- Clip to fix the film directly to the turntable
- Weighing system
- Brake for Roll Container