


© C-One PLUS



PLC CONTROLLED



STANDARD TURNTABLE:
1650MM/2000KG



STURDINESS



C-One Plus is really versatile and virtually indestructible. It is the perfect solution for peculiar needs in wrapping pallets.

The structure and the turntable thickness allow to wrap pallets up to 2000 kg and intense work.

With C-One Plus strength and flexibility are all in one: the cycle control is made by PLC, therefore with a huge number of process variables controls.

The electronic components are exclusively from major suppliers, guaranteeing our customers greater reliability and spare parts availability worldwide.

The "rack and pinion" system for the carriage movement is an exclusive innovation of C-One, for a great safety and toughness of the machines.

Thanks to the wide choice of options C-One Plus can be adapted to every needs.

Technical Data



- ↕ Height: 2468 mm.
- ↔ Width: 1650 mm.
- ↗ Length: 2454 mm.
- ↑ Turntable height from ground level: 86 mm.
- 📦 Weight: 500 kg.
- 🔌 Power Supply: 400 Vac 3PH+N
(other options: 220 Vac 3PH+N o 220 Vac 1P+N)
- ⚡ Power absorption: 0,62 KW

Product Specifications



- Machine cycle controlled by Siemens PLC
- Frequency controller to adjust separately the ascent and descent speed of the carriage
- Frequency controller to adjust the turntable speed
- Turntable ø.1650 mm
- Maximum pallet height: 2300 mm
- Maximum pallet dimensions 1000x1200 mm
- Maximum pallet weight 2000 kg
- Electromagnetic brake to stretch the film
- Photocell to detect the height of the pallet
- Safety stop at the bottom of the carriage
- Stop at 0 position
- IP54 control panel
- 3 Password levels
- Adjustable parameters by the control panel without password: cycle selection, number of laps (bottom and top), topsheet cycle parameters, rotation speed, carriage ascent speed, carriage descent speed, wrapping height in cm, film tension, initial wrapping height
- 5 Working cycles: ascent/descent; topsheet; only ascent; only descent; layers
- Storage of 6 user programs
- 3 Operating modes: semimanual, semiautomatic, fixed height
- Strengthening operation
- Acoustic warning at the cycle beginning and stop
- Auto diagnostic
- Wrapped pallet counter (with password)
- Full configuration possible at 3rd password level
- Infrared/radio remote control receiver
- Powder coating
- Still turntable at the end of the cycle
- 2 Years warranty

Main Options

- Electrical top-press unit for unstable loads
- Power pre-stretch carriage
- Wrapping height up to 2.8 mt
- 1800 mm diameter turntable
- 2000 kg load
- Remote Control
- Ramp
- Pit frame
- Black loads photocell
- Clip to fix the film directly to the turntable
- Weighing system
- Brake for Roll Container
- Fork-shaped turntable